



LISTING INFORMATION OF

**DreamCast Match Lit Firepit with Standing Pilot 60K - 250K
BTU**

SPEC ID: 71301

DreamCast Design and Production Ltd.
2200 Vauxhall Place
Richmond, BC V6V 1Z9
Canada

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

PRODUCT DESCRIPTION

Product	Outdoor Decorative Gas Appliances	
Brand Name	DreamCast design and production	
Description	The products covered in this report are outdoor decorative match lit gas firepits, bowls and tables featuring a standing pilot with safety shut-off	
Models	<u>Outdoor Decorative Gas Bowls</u> LOTUS32-NG-CFB60, LOTUS32-LP-CFB60, AURA36-NG-CFB60, AURA36-LP-CFB60, AURA48-NG-CFB60, AURA48-LP-CFB60, AURA48-NG-CFB120, AURA48-LP-CFB120, AURA48-NG-CFB180, AURA48-LP-CFB180, LOTUS45-NG-CFB60, LOTUS45-LP-CFB60, LOTUS45-NG-CFB120, LOTUS45-LP-CFB120, LOTUS45-NG-CFB180, LOTUS45-LP-CFB180, ZEN34-NG-CFB60, ZEN34-LP-CFB60, ZEN34-NG-CFB120, ZEN34-LP-CFB120, ZEN34-NG-CFB180, ZEN34-LP-CFB180, ZEN36-NG-CFB60, ZEN36-LP-CFB60, ZEN36-NG-CFB120, ZEN36-LP-CFB120, ZEN36-NG-CFB180, ZEN36-LP-CFB180, ZEN48-NG-CFB60, ZEN48-LP-CFB60, ZEN48-NG-CFB120, ZEN48-LP-CFB120, ZEN48-NG-CFB180 and ZEN48-LP-CFB180	
	<u>Outdoor Decorative Gas Tables</u> BLOQ-NG-CFB60, BLOQ-LP-CFB60, ELEMENT36-NG-CFB60, ELEMENT36-LP-CFB60, ELEMENT48-NG-CFB60, ELEMENT48-LP-CFB60, ELEMENT48-NG-CFB120, ELEMENT48-LP-CFB120, ELEMENT48-NG-CFB180, ELEMENT48-LP-CFB180, LIBRA48-NG-CFB60, LIBRA48-LP-CFB60, LIBRA60-NG-CFB60, LIBRA60-LP-CFB60, LIBRA60-NG-CFB120, LIBRA60-LP-CFB120, LIBRA60-NG-CFB180, LIBRA60-LP-CFB180, LIBRA72-NG-CFB60, LIBRA72-LP-CFB60, LIBRA72-NG-CFB120, LIBRA72-LP-CFB120, LIBRA72-NG-CFB180, LIBRA72-LP-CFB180, QUADRA48-NG-CFBL110, QUADRA48-LP-CFBL110, QUADRA60-NG-CFBL150, QUADRA60-LP-CFBL150, QUADRA72-NG-CFBL210, QUADRA72-LP-CFBL210, QUADRA84-NG-CFBL250 and QUADRA84-LP-CFBL250	
	<u>Outdoor Decorative Gas Fire Pits</u> CUBO-NG-CFB60, CUBO-LP-CFB60, LINEA48-NG-CFBL110, LINEA48-LP-CFBL110, LINEA60-NG-CFBL190, LINEA60-LP-CFBL190, LINEA72-NG-CFBL250, LINEA72-LP-CFBL250, PHANTOM48-NG-CFBL150, PHANTOM48-LP-CFBL150, PHANTOM60-NG-CFBL210, PHANTOM60-LP-CFBL210, PHANTOM72-NG-CFBL250 and PHANTOM72-LP-CFBL250	
Model Similarity	LOTUS32, LOTUS45, AURA36, AURA48, ZEN34, ZEN36, ZEN48, BLOQ, ELEMENT36, ELEMENT48, LIBRA48, LIBRA60, LIBRA72, QUADRA48, QUADRA 60, QUADRA72, QUADRA 84, CUBO, LINEA48, LINEA60, LINEA72, PHANTOM48, PHANTOM60 and PHANTOM72	Concrete Enclosure Type and Size
	NG	Natural Gas Model
	LP	Propane Gas Model

CFB60, CFB120, CFB180, CFBL110, CFBL120, CFBL150,
CFBL210 and CFBL250Burner Type
and Size**APPLIANCE RATINGS**

	Natural Gas	Propane
Minimum Supply Pressure	7" w.c.	11" w.c

Burner	Orifice Size/# of Burner Jets	
	Natural Gas	Propane
CFB60	#53 DMS x 5/Jets	#61 DMS x 5/Jets
CFB120	#53 DMS x 10/Jets	#61 DMS x 10/Jets
CFB180	#53 DMS x 16/Jets	#61 DMS x 16/Jets
CFBL110	#53 DMS x 11/Jets	#61 DMS x 11/Jets
CFBL150	#53 DMS x 15/Jets	#61 DMS x 15/Jets
CFBL190	#53 DMS x 19/Jets	#61 DMS x 19/Jets
CFBL210	#53 DMS x 21/Jets	#61 DMS x 21/Jets
CFBL250	#53 DMS x 25/Jets	#61 DMS x 25/Jets

Model	Input Rate (Btu/hr)	
	Natural Gas	Propane
LOTUS32-NG/LP-CFB60	85,000	62,000
AURA36-NG/LP-CFB60	85,000	62,000
AURA48-NG/LP-CFB60	85,000	62,000
AURA48-NG/LP-CFB120	130,000	110,000
AURA48-NG/LP-CFB180	165,000	160,000
LOTUS45-NG/LP-CFB60	85,000	62,000
LOTUS45-NG/LP-CFB120	130,000	110,000
LOTUS45-NG/LP-CFB180	165,000	160,000
ZEN34-NG/LP-CFB60	85,000	62,000
ZEN34-NG/LP-CFB120	130,000	110,000
ZEN34-NG/LP-CFB180	165,000	160,000
ZEN36-NG/LP-CFB60	85,000	62,000
ZEN36-NG/LP-CFB120	130,000	110,000
ZEN36-NG/LP-CFB180	165,000	160,000
ZEN48-NG/LP-CFB60	85,000	62,000
ZEN48-NG/LP-CFB120	130,000	110,000
ZEN48-NG/LP-CFB180	165,000	160,000
BLOQ-NG/LP-CFB60	85,000	62,000
ELEMENT36-NG/LP-CFB60	85,000	62,000
ELEMENT48-NG/LP-CFB60	85,000	62,000
ELEMENT48-NG/LP-CFB120	130,000	110,000
ELEMENT48-NG/LP-CFB180	165,000	160,000

Model	Input Rate (Btu/hr)	
	Natural Gas	Propane
LIBRA48-NG/LP-CFB60	85,000	62,000
LIBRA60-NG/LP-CFB60	85,000	62,000
LIBRA60-NG/LP-CFB120	130,000	110,000
LIBRA60-NG/LP-CFB180	165,000	160,000
LIBRA72-NG/LP-CFB60	85,000	62,000
LIBRA72-NG/LP-CFB120	130,000	110,000
LIBRA72-NG/LP-CFB180	165,000	160,000
QUADRA48-NG/LP-CFBL110	155,000	135,000
QUADRA60-NG/LP-CFBL150	160,000	160,000
QUADRA72-NG/LP-CFBL210	215,000	215,000
QUADRA84-NG/LP-CFBL250	275,000	245,000
CUBO-NG/LP-CFB60	85,000	62,000
LINEA48-NG/LP-CFBL110	155,000	135,000
LINEA60-NG/LP-CFBL190	180,000	190,000
LINEA72-NG/LP-CFBL250	275,000	245,000
PHANTOM48-NG/LP-CFBL150	160,000	160,000
PHANTOM60-NG/LP-CFBL210	215,000	215,000
PHANTOM72-NG/LP-CFBL250	275,000	245,000

CLEARANCES TO COMBUSTIBLE CONSTRUCTION

BOWL MODELS LOTUS 32, AURA 36, AURA 48, ZEN 34, ZEN 36 and ZEN 48	
From the Burner	36 inches all around
Floor	0 Inches

TABLE MODELS BLOQ, ELEMENT 36, ELEMENT 48, LIBRA 48, LIBRA 60, LIBRA 72, QUADRA 48, QUADRA 72 AND QUADRA 84	
Gas Control Side	48 inches from the burner
End	36 inches from the burner
Floor	0 Inches

FIREPIT MODELS CUBO, LINEA 48, LINEA 60, LINEA 72, PHANTOM 48, PHANTOM 60 AND PHANTOM 72	
Gas Control Side	48 inches from the burner
End	36 inches from the burner
Floor	0 Inches

Attribute	Value
Criteria	ANSI Z21.97:2017 Ed.3
Criteria	CSA 2.41:2017 Ed.3
CSI Code	10 30 00 Fireplaces and Stoves
Fuel Type	Propane
Fuel Type	Natural Gas
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	GAS-FIRED APPLIANCES FOR OUTDOOR INSTALLATION
Spec ID	71301